In accordance to Annex III of Regulation (EU) Nr. 305/2011



LE-H53545-04 ZIB 45



Purpose

- · Underlays for discontinuous roofing
- Suitable for under-roof construction with increased requirements

Name, contact producer

BÜSSCHER & HOFFMANN GmbH A-4470 (AT) Fabrikstraße 2 Tel.: +43 (7223) 823 23-0 Web: www.bueho.com E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system3 EN 13859-1:2014

Harmonized standard EN 13859-1:2014

Declared performance

| | | Harmonized technical |
|---|--------------------------------|----------------------|
| Essential characteristics | Performance | specification |
| Reaction to fire test | E | EN 13859-1:2014 |
| Tensile force long./trans. | 1000/800 (±200/±100) N/50mm | EN 13859-1:2014 |
| Elongation at single-end breaking force | 50/50 (±10/±10) % | EN 13859-1:2014 |
| Resistance to tearing (nail shank) long./trans. | 220/220 (±50/±50) N | EN 13859-1:2014 |
| Flexibility at low temperatures | -20 °C | EN 13859-1:2014 |
| Resistance to water penetration | W1 | EN 13859-1:2014 |
| Artificial aging - resistance to water penetration | W1 | EN 13859-1:2014 |
| Artificial aging - tensile strength | 1100/800 (±300/±200) N/50mm | EN 13859-1:2014 |
| Artificial aging - elongation at single-end breaking force long./trans. | NPD | EN 13859-1:2014 |
| Hazardous substances | Keine | EN 13859-1:2014 |

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by

and hounds

Bmstr. Dipl. Ing. Karl Landl

General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.

Issue date: 13.01.2024 Page 1 / 1