

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. Identification code of the product-type

LE-H94051-02**Büsscher GMS-Noppenbahn 08/1.0****Purpose**

- Waterproofing membrane with moisture barrier and ventilation type V

Name, contact producer

BÜSSCHER & HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 (7223) 823 23-0

Web: www.bueho.com

E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system2+

EN 13967:+A1:2017

Harmonized standard

EN 13967:+A1:2017

Notified body

0799 KIWA MPA Bautest GmbH, TBU Gutenbergstraße 29 , D-48268 Greven

Certificate of conformity

0799-CPR-304

Declared performance

| Essential characteristics | Performance | Harmonized technical specification |
|--|-------------------------------------|------------------------------------|
| Watertightness | wasserdicht W1 | EN 13967:+A1:2017 |
| Reaction to fire test | E | EN 13967:+A1:2017 |
| Tensile force long./trans. | ≥ 310 / ≥ 260 N/50 mm | EN 13967:+A1:2017 |
| Resistance to static loading | keine Perforation bei 20 kg/24 h | EN 13967:+A1:2017 |
| Shear resistance of joints | NPD | EN 13967:+A1:2017 |
| Durability of waterproofness to artificial aging | wasserdicht | EN 13967:+A1:2017 |
| Durability of waterproofness to artificial chemicals | wasserdicht | EN 13967:+A1:2017 |
| Resistance to impact | ≥ 450 mm | EN 13967:+A1:2017 |
| Resistance to tearing (nail shank) | ≥ 215 / ≥ 225 N | EN 13967:+A1:2017 |
| Hazardous substances | NPD | EN 13967:+A1:2017 |

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



Bmstr. Dipl. Ing. Karl Landl
General Manager

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.