

Certificate of Conformity of the Factory Production Control 1213–CPR–018

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

O.C.-Plan 1015, 1018, 1020, 1025, 1030, black	1,5 mm, 1,8 mm, 2,0 mm, 2,5 mm, 3,0 mm
O.C.-Plan 1015, black with silver coated surface	1,5 mm
O.C.-Plan 1018, black with silver coated surface	1,8 mm
O.C.-Plan 1020, black with silver coated surface	2,0 mm
O.C.-Plan 1025, black with silver coated surface	2,5 mm
O.C.-Plan 1030, black with silver coated surface	3,0 mm
O.C.-Plan 3018, 3020, 3025, 3030, black	1,8 mm, 2,0 mm, 2,5 mm, 3,0 mm
O.C.-Plan 4230, black	2,0 mm
O.C.-Plan 5028 SK, black	2,0 mm
Polyfin® 1020, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 3016, 3016 FR Colour (et al. light grey, grey, black, red, green, blue, white)	1,6 mm
Polyfin® 3016 SP-M, Colour (et al. blue, light blue, white)	1,6 mm
Polyfin® 3018, 3018 FR Colour (et al. light grey, grey, black, red, green, blue, white)	1,8 mm
Polyfin® 3020, 3020 FR Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 3023, Colour (et al. light grey, grey, black, red, green, blue, white)	2,3 mm
Polyfin® 3025, Colour (et al. light grey, grey, black, red, green, blue, white)	2,5 mm
Polyfin® 3030, Colour (et al. light grey, grey, black, red, green, blue, white)	3,0 mm
Polyfin® 4120 PP, Colour (et al. light grey)	1,8 mm
Polyfin® 4230, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 5024 SK, Colour (et al. light grey, grey, black, red, green, blue, white)	1,6 mm
Polyfin® 5028 SK, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Atlantic® 301, Colour (et al. light grey, grey, black)	2,0 mm
Atlantic® 401, Colour (et al. light grey, grey, black)	2,0 mm

Flexible sheets for waterproofing - Plastic damp proof sheets including plastic basement tanking sheets made of Ethylene Copolymer Bitumen (ECB) or of flexible polyolefins (FPO)

Intended use: damp proof sheets TYPE A and basement tanking sheets TYPE T
 produced by or for

POLYFIN AG

Polyfinstraße 1
 74909 Meckesheim

and produced in the manufacturing plants

0015

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13967:2012

under system 2+ for the performances set out in this certificate are applied and that

the factory production control fulfils all the prescribed requirements for these performances.

This certificate was first issued on 2006-10-18 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard(s), used to assess the performance of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the factory production control certification body.




 i. V.

Dipl.-Ing. Helmut Zanzinger
 Certification Body

Würzburg, 19 June 2015