

8018/000-02

Polyfin Kontakkleber W

Product	POLYFIN Contact Adhesive W is a ready-to-use, solvent-based contact adhesive based on synthetic rubber.
Intended use	Contact bonding of unlaminated / unbacked Polyfin® sealing membranes to substrates such as concrete, masonry, skylight elements, suitable metals, etc.
Application	Polyfin Contact Adhesive W must be stirred well before use and applied to both sides, avoiding pockets of adhesive. The substrate must be clean, free of dust and grease, and free of any residues that could affect adhesion. After applying the adhesive, allow it to dry for approx. 5 to 20 minutes. After this time, the adhesive film should still feel slightly sticky to the touch but no longer damp. Corrections after bonding are no longer possible. Apply the adhesive to both sides with a brush, lambskin roller, or notched trowel. The optimum processing temperature is +15°C to +25°C, not below 5°C!
Consumption	approx. 330 g/m ² per side (total 660 g/m ²)
open time	Approximately 30 minutes (depending on the drying time)
Storage and transportation	Shelf life: Approximately 12 months in unopened original containers when stored between +5 and +25°C. The containers must be stored and transported upright and secured against falling over.
Cleaning	Clean application equipment with pure gasoline immediately after use.
Safety instructions	Wear solvent-resistant protective gloves and safety goggles. Only use in well-ventilated areas. Adhesive is highly flammable, so keep away from sources of ignition and do not smoke. Labeling according to hazardous substances regulations: see safety data sheet.
Important instructions	Our supplier guarantees the consistently high quality of its products. All information is based on tests and many years of practical experience. The variety of materials used and different working conditions, which we cannot influence, exclude any claims based on this information. We therefore recommend that you carry out sufficient tests of your own before starting work. In addition, we are happy to provide technical advice.
Application	9 kg container

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

Subject to alteration without notice.

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

Development, Production and Sales of our products according to ISO 9001.